



**PACKWAY INC.**  
**緯華企業股份有限公司**  
緯華用心 精緻創新



*We pack your way*

*Strapping Machine Series*



ISO 9001  
FM57756



台灣精品  
TAMAC EXCELLENCE



## Fully Automatic Models



PW-0860AS2R

### Options

- Detection for strap not in position
- Detection for no strap
- Stainless steel structure SUS #304
- Single phase (1Ø)



PW-0860CS2R

### PW-0860AS2R/ PW0860CS2R Fully Automatic Strapping Machine

AS2R: Roller Table Drive + 2 Sensors with Steel Arch

CS2R: Roller Table Drive + 2 Sensors with Aluminum Arch

Power	3Ø, 220/380/415/440V, 50/60Hz
Standard Arch Size	W 850 x H 600 mm (other sizes made on request)
Strapping Size (Min.)	L 350 x W 400 x H 30 mm
Strap Width	9, 12, 15, 19 mm (PET option)
Strapping Tension	0 ~ 70 Kgs
Strapping Speed	2.4 sec./strap (25 strap/min.)
Sealing point	692 mm from the floor
Working Height	810 mm
Machine Size	L 1645 x W 670 x H 1535 mm



PW-0860AS2B

### Options

- Detection for strap not in position
- Detection for no strap
- Stainless steel structure SUS #304
- Single phase (1Ø)



PW-0860CS2B

### PW-0860AS2B/ PW0860CS2B Fully Automatic Strapping Machine

AS2B: Belt Table Drive + 2 Sensors with Steel Arch

CS2B: Belt Table Drive + 2 Sensors with Aluminum Arch

Power	3Ø, 220/380/415/440V, 50/60Hz
Standard Arch Size	W 850 x H 600 mm (other sizes made on request)
Strapping Size (Min.)	L 200 x W 200 x H 30 mm
Strap Width	9, 12, 15, 19 mm (PET option)
Strapping Tension	0 ~ 70 Kgs
Strapping Speed	2.4 sec./strap (25 strap/min.)
Working Height	810 mm
Machine Size	L 1645 x W 760 x H 1535 mm



*I am from Taiwan*

🏠 56, 35th Road. Taichung Industrial Park,  
Taichung 407, TAIWAN, R.O.C  
☎ +886 4 2359 1858  
📠 +886 4 2359 7489  
🌐 [www.packway.com](http://www.packway.com)