



PACKWAY INC.
緯華企業股份有限公司
緯華用心 精緻創新



We pack your way

Strapping Machine Series



ISO 9001
FM57756



台灣精品
TAMAC EXCELLENCE





PW-0860LS2R

Options

- Detection for strap not in position
- Detection for no strap
- Stainless steel structure SUS #304



PW-0860CLS2R

PW-0860LS2R/ PW0860CLS2R Fully Automatic Strapping Machine

LS2R: Roller Table Drive + 2 Sensors with Steel Arch in Low Profile

CLS2R: Roller Table Drive + 2 Sensors with Aluminium Arch in Low Profile

Power	3Ø, 220/380/415/440V, 50/60Hz
Standard Arch Size	W 850 x H 600 mm (other sizes made on request)
Strap Width	9, 12, 15,19 mm (PET option)
Strapping Tension	0 ~ 70 Kgs
Strapping Speed	2.4 sec./strap (25 strap/min.)
Working Height	450 mm
Machine Size	L 2260 x W 760 x H 1774 mm



PW-0860YS2

Options

- Detection for strap not in position
- Detection for no strap
- Stainless steel structure SUS #304
- Conveyor system (custom made)
- Sensor for 2 straps
- No power roller



PW-0860CYS2

PW-0860YS2/ PW0860CYS2 Automatic Strapping Machine

Y: Side Seal + 2 Sensors with Steel Arch

CY: Side Seal + 2 Sensors with Aluminum Arch

Power	3Ø, 220/380/415/440V, 50/60Hz
Standard Arch Size	W 600 x H 850 mm (other sizes made on request)
Strap Width	9, 12, 15,19 mm (PET option)
Strapping Tension	0 ~ 70 Kgs
Strapping Speed	2.4 sec./strap (25 strap/min.)
Sealing point	692 mm from the floor
Machine Size	L 1425 x W 630 x H 1724 mm



I am from Taiwan

🏠 56, 35th Road. Taichung Industrial Park,
Taichung 407, TAIWAN, R.O.C
☎ +886 4 2359 1858
📠 +886 4 2359 7489
🌐 www.packway.com