



## ST 10<sup>(3/8")</sup>-13<sup>(1/2")</sup>-16<sup>(5/8")</sup>-19<sup>(3/4")</sup>

### PNEUMATIC STRAPPING TOOL FOR STEEL STRAP WITH SEAL FLAT AND ROUND SURFACES

#### TECHNICAL DATA / APPLICATIONS :

Very light and compact strapping tool, easy to use and set. Strong and reliable to use in industrial medium / light applications, is available in different configurations. The standard version is equipped by push button, on demand is also available the choke collar version. Available in four strap sizes: 10mm (3/8"); 13mm(1/2"); 16mm(5/8"); 19mm(3/4")

Package type	Flat, round and irregular surfaces
Strap quality	Bright- blue- high tensile
Strap Width	From 10mm to 19mm (3/8" - 3/4")
Strap thickness bright—blue Rmax= 850 N/mm <sup>2</sup>	From 0,4mm up to 0,8mm (0.016" - 0.031")
Strap thickness high tensile Rmax= 1100 N/mm <sup>2</sup>	From 0,4mm up to 0,63mm (0.016" - 0.025")
Max. tension	From 1500 N up to 4500 N (depends by motor)
Air pressure and consumption	From 5,5 up to 6,5 bar MAX / 12 l/s
Max. tensioning speed	From 5 mt/min up to 11 mt/min
Joint type	With seal—single notch
Seal type	Overlap min. seal lenght 22mm (7/8")
Weight	Around 4 Kg



CHOKE COLLAR MODEL

PUSH BUTTON MODEL

- MODERN DESIGN
- LIGHT AND ERGONOMIC
- DIFFERENT CONFIGURATIONS
- EASY TO USE
- NEW PNEUMATIC BOSCH MOTORS

MODEL		ORDER CODES	
ST 10 BUTTON	1500 N	101.100.310	ON REQ.
ST 10 CHOKE COLLAR	1500 N	101.100.320	ON REQ.
ST 13 BUTTON	3000 N	101.130.410	STANDARD
ST 13 CHOKE COLLAR	3000 N	101.130.420	ON REQ.
ST 16 BUTTON	3000 N	101.160.410	STANDARD
ST 16 CHOKE COLLAR	3000 N	101.160.420	ON REQ.
ST 16 BUTTON	4500 N	101.160.510	ON REQ.
ST 16 CHOKE COLLAR	4500 N	101.160.520	ON REQ.
ST 19 BUTTON	3000 N	101.190.410	STANDARD
ST 19 CHOKE COLLAR	3000 N	101.190.420	ON REQ.
ST 19 BUTTON	4500 N	101.190.510	STANDARD
ST 19 CHOKE COLLAR	4500 N	101.190.520	ON REQ.

SIAT S.p.A. Via Puecher, 22 - 22078 Turate (CO) Italy • Tel +39.02.964951 • Fax +39.02.9689727

www.siat.com • www.columbiatools.it • www.maillis.gr • siat@siat.com