



STTR 19(3/4")-25(1")-32(1-1/4")

PNEUMATIC TENSIONER FOR STEEL STRAP WITH SEAL — FLAT AND ROUND SURFACE— USING WITH SEALERS MODEL STP / STPM

TECHNICAL DATA / APPLICATIONS :

Pneumatic tensioner easy to use and set. Strong and reliable to use in industrial heavy applications. Available standard with push button version is also supplying, on demand, in choke collar version. The particular conformation is able to use straps from 19mm(3/4") up to 32mm(1-1/4") without any adjustments.

| | |
|---------------------------------|--|
| Package type | Flat, round and irregular surfaces |
| Strap quality | Bright- blue—high tensile Rmax=1100 N/mm2 |
| Strap Width | From 19mm up to 32mm (3/4" - 1.1/4") |
| Strap thickness | From 0,6 up to 1,1mm (0.024" - 0.043") |
| Max. tension | Around 9000 N |
| Air pressure and consumption | from 5 up to 6,5 bar MAX / 12 Lt/sec |
| Max. tensioning speed | Around 6 mt / min |
| Weight | Around 4,1 Kg (button) - 4,3 Kg (choke collar) |
| Order code push button version | 104.990.110 |
| Order code choke collar version | 104.990.120 |



PUSH BUTTON VERSION



CHOKE COLLAR VERSION

- ERGONOMIC AND MODERN DESIGN
- LIGHT AND COMPACT
- EASY TO USE
- EQUIPPED BY BOSCH PNEUMATIC MOTORS

SIAT S.p.A. Via Puecher, 22 - 22078 Turate (CO) Italy • Tel +39.02.964951 • Fax +39.02.9689727

www.siat.com • www.columbiatools.it • www.maillis.gr • siat@siat.com